

HT7 & HT9 Series Heating Tapes

UP TO 450°C
GLASS FIBRE INSULATION



Linear Loading: 164W per metre (50W per foot).
Surface Loading: 0.62Wper cm² (4Wper in²)

Voltages: 115 or 230 volts. (732cm and 976cm length – 230V only).

Mains Connection is provided at one end for ease of installation. The lead length is 9cm (3.5”).

Construction: Constructed of high temperature resistant glass. Two layers of glass fabric protect the inorganic core double glass covered heating element. Safe for applying to metal pipes. The HT9 elements are braided with earth (ground) wire.

Applications: Intimate flat contact with the surface to be heated is achieved with the specially engineered free moving and self adjusting elements which accept the contours of the pipe. The tapes are however not water-resistant and should always be used in dry conditions and never used for outdoors applications.

Secure Fixing: Eyelets and tie-cord provide secure fixing.

Control: A thermostat or suitable controller (MC5, MC227 or MC810B) should always be used.

<i>Standard Width 25 mm (1”)</i>					
<i>Length</i>		<i>Volts</i>	<i>Watts</i>	<i>Catalogue Number</i>	<i>Catalogue Number</i>
<i>cm</i>	<i>Feet</i>				
<i>61</i>	<i>2</i>	<i>115or230</i>	<i>100</i>	<i>HT75502</i>	<i>HT95502</i>
<i>91</i>	<i>3</i>	<i>115or230</i>	<i>150</i>	<i>HT75503</i>	<i>HT95503</i>
<i>122</i>	<i>4</i>	<i>115or230</i>	<i>200</i>	<i>HT75504</i>	<i>HT95504</i>
<i>183</i>	<i>6</i>	<i>115or230</i>	<i>300</i>	<i>HT75506</i>	<i>HT95506</i>
<i>244</i>	<i>8</i>	<i>115or230</i>	<i>400</i>	<i>HT75508</i>	<i>HT95508</i>
<i>366</i>	<i>12</i>	<i>115or230</i>	<i>600</i>	<i>HT75512</i>	<i>HT95512</i>
<i>488</i>	<i>16</i>	<i>115or230</i>	<i>800</i>	<i>HT75516</i>	<i>HT95516</i>
<i>732</i>	<i>24</i>	<i>230</i>	<i>1200</i>	<i>HT75524</i>	<i>HT95524</i>
<i>976</i>	<i>32</i>	<i>230</i>	<i>1600</i>	<i>HT75532</i>	<i>HT95532</i>

**HT 7 is the same as the HT9 but without the earth (ground) braid.*