

# Spectrophotometers

## 6300 and 6320D Visible Spectrophotometers

- Wavelength range of 320 to 1000nm
- Absorbance, %T and concentration modes
- Multi-parameter display with wavelength and photometric readouts
- Wide range of sampling accessories
- Domed lid of 6320D accepts tubes up to 105mm tall

The 6300 is a high quality, low cost unit for spectrophotometric applications in schools and colleges, as well as in QC and testing procedures for a wide variety of services and industries. The 6320D is based on the 6300 platform and includes a domed lid which accepts taller tubes up to a height of 105mm.

### Technical Specification

#### Wavelength

Range	320 to 1000nm
Resolution	1nm
Accuracy	±2nm
Spectral bandwidth	8nm

#### Photometrics

Transmittance	0 to 199.9%T
Absorbance	-0.300 to 1.999A
Accuracy	±1%T
Resolution	0.1%T, 0.001A
Stray light	<0.5%T
Noise	<1%
Stability	1%/h after 15 minutes

#### Concentration

Range	-300 to 1999
Resolution	0.1 to 1
Units	ppm, mg/l, g/l, M, %, blank
Factor	0 to 199.9, 1000 to 9999

#### Other

Light source	Tungsten halogen lamp
Outputs	Analogue and RS232
Power	<50W
Size (w x d x h)	365 x 272 x 160mm
Weight	6kg



6300

### Ordering Information

Part Code	Description
630 501	6300 visible spectrophotometer supplied with mains lead, pack 100 disposable cuvettes, 10 x 10mm cell holder, interface cable and PC application software on CD-ROM* (230V/50Hz)
632 501	6320D visible spectrophotometer supplied with mains lead and dual cell holder (for 10mm square cuvettes and 12.7mm diameter tubes) (230V/50Hz)

\* requires free on-line registration